

Safety data sheet

Page: 1/15

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ultrafuse® ASA Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

| Recommended use: 3D Printing

1.3. Details of the supplier of the safety data sheet

Company:
BASF 3D Printing Solutions B.V.
Eerste Bokslootweg 17
7821 AT Emmen, Netherlands

Contact address:
BASF SE
67056 Ludwigshafen
GERMANY

Telephone: +49 621 60-0
E-mail address: global.info@basf.com

1.4. Emergency telephone number

International emergency number:
Telephone: +49 180 2273-112

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

No need for classification according to GHS criteria for this product.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

The product does not require a hazard warning label in accordance with GHS criteria.

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

The product may cause burns, if handled in the melted state.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

| Preparation based on: Polymer, additives

Regulatory relevant ingredients

| 2-(2H-Benzotriazol-2-yl)-p-cresol

| Content (W/W): > 0 % - < 1 %

| CAS Number: 2440-22-4

| EC-Number: 219-470-5

| REACH registration number: 01-2119583811-34

Skin Sens. 1B

Aquatic Chronic 1

M-factor chronic: 1

H317, H410

| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

Content (W/W): > 0 % - < 1 %	Eye Dam./Irrit. 1
CAS Number: 52829-07-9	Aquatic Acute 1
EC-Number: 258-207-9	Aquatic Chronic 2
REACH registration number: 01-2119537297-32	Repr. 2 (fertility)
	M-factor acute: 1
	H318, H361f, H411, H400

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water. If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth immediately with water. Immediate medical attention required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

| water spray, foam, dry powder, carbon dioxide

5.2. Special hazards arising from the substance or mixture

| Endangering substances: carbon oxides

| Advice: The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Special protective equipment:

| Wear a self-contained breathing apparatus.

Further information:

| Dust can form an explosive mixture with air. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

| Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

6.1. Personal precautions, protective equipment and emergency procedures

| No special precautions necessary.

6.2. Environmental precautions

| Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

| For small amounts: Sweep/shovel up.

| For large amounts: Sweep/shovel up.

| Dispose of absorbed material in accordance with regulations. Avoid raising dust.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
 Date previous version: 15.02.2022
 Date / First version: 05.08.2021
 Product: **Ultrafuse® ASA Black**

Version: 3.0
 Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Protection against fire and explosion:

The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Avoid deposition of dust. Avoid extreme heat.

Storage stability:

Protect against moisture.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

The substances mentioned are contained only in traces in the product. The release and quantity of the stated substance is dependent on the processing conditions.

100-41-4: ethylbenzene

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 884 mg/m³ ; 200 ppm (OEL (EU))

indicative

TWA value 442 mg/m³ ; 100 ppm (OEL (EU))

indicative

100-42-5: styrene

107-13-1: acrylonitrile

Skin Designation (Directive 2004/37/EC)

The substance can be absorbed through the skin.

TWA value 1 mg/m³ ; 0.45 ppm (Directive 2004/37/EC)

The expiration date of this limit: 05 April 2026

STEL value 4 mg/m³ (Directive 2004/37/EC)

STEL value 1.8 ppm (Directive 2004/37/EC)

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

141-32-2: n-butyl acrylate

STEL value 53 mg/m³ ; 10 ppm (OEL (EU))
indicative

TWA value 11 mg/m³ ; 2 ppm (OEL (EU))
indicative

8002-74-2: Paraffin waxes and Hydrocarbon waxes

8.2. Exposure controls

Appropriate engineering controls

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift. When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: solid
Form: filament
Colour: black

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
 Date previous version: 15.02.2022
 Date / First version: 05.08.2021
 Product: **Ultrafuse® ASA Black**

Version: 3.0
 Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

Odour:	odourless
Odour threshold:	not applicable, odour not perceivable
Melting point:	> 150 °C
Boiling point:	not applicable
Flammability:	Not a flammable solid according to UN transport regulations division 4.1 and GHS chapter 2.7.
Lower explosion limit:	For solids not relevant for classification and labelling.
Upper explosion limit:	For solids not relevant for classification and labelling.
Flash point:	not applicable, the product is a solid
Auto-ignition temperature:	not applicable
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated. Prolonged thermal loading can result in products of degradation being given off.
pH value:	not applicable, substance/mixture is non-soluble (in water)
Solubility in water:	insoluble
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures
Vapour pressure:	not determined
Relative density:	1.07 (20 °C)
Density:	1.07 g/cm ³ (20 °C)
Relative vapour density (air):	The product is a non-volatile solid.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of spontaneous heating.

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

Corrosion to metals

| No corrosive effect on metal.

Other safety characteristics

| Evaporation rate:
The product is a non-volatile solid.

SECTION 10: Stability and Reactivity

10.1. Reactivity

| No hazardous reactions if stored and handled as prescribed/indicated.

| Corrosion to metals: No corrosive effect on metal.

10.2. Chemical stability

| The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

| No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

| Temperature: > 300 °C
Prolonged exposure to elevated temperatures may result in exothermic decomposition accompanied by a pressure build-up in sealed containers. Avoid all sources of ignition: heat, sparks, open flame.

10.5. Incompatible materials

Substances to avoid:
| oxidizing agents

10.6. Hazardous decomposition products

| Hazardous decomposition products:
Prolonged thermal loading can result in products of degradation being given off., monomers, gases/vapours, oxides, hydrocarbons, cyclic low molecular weight oligomers

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Contact with molten product may cause thermal burns.

Experimental/calculated data:

(oral):No applicable information available.

(by inhalation):The inhalation of dusts represents a potential acute hazard.

(dermal):No applicable information available.

Irritation

Assessment of irritating effects:

Not irritating to eyes and skin. May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

Developmental toxicity

Assessment of teratogenicity:

| Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

| Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

| Based on available data, the classification criteria are not met.

Aspiration hazard

| not applicable

Interactive effects

No data available.

11.2. Information on other hazards

Other information

Other relevant toxicity information

The product has been assessed on the basis of the components' available data. To some extent data gaps exist for individual components. According to our present knowledge and experience dangers which are not covered by the current labeling are not to be expected.

SECTION 12: Ecological Information

12.1. Toxicity

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

Assessment of aquatic toxicity:

Based on available data, the classification criteria are not met. At the present state of knowledge, no negative ecological effects are expected.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

The product has not been tested.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Adsorption to solid soil phase is expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria.

12.6. Endocrine disrupting properties

12.7. Other adverse effects

The product does not contain substances that are listed in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

12.8. Additional information

Add. remarks environm. fate & pathway:

Due to the consistency of the product, dispersion into the environment is impossible. Therefore no negative effects on the environment may be anticipated based on the present state of knowledge.

Other ecotoxicological advice:

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

The product has been assessed on the basis of the components' available data. To some extent data gaps exist for individual components. According to our present knowledge and experience dangers which are not covered by the current labeling are not to be expected.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Dispose of in accordance with national, state and local regulations.
Contact specialized companies about recycling.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport

ADN

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
 Date previous version: 15.02.2022
 Date / First version: 05.08.2021
 Product: **Ultrafuse® ASA Black**

Version: 3.0
 Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
Date previous version: 15.02.2022
Date / First version: 05.08.2021
Product: **Ultrafuse® ASA Black**

Version: 3.0
Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
| Listed in above regulation: no

| If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

| Product is not classified as hazardous.

| Chemical Safety Assessment not required

SECTION 16: Other Information

| Any other intended applications should be discussed with the manufacturer.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

| Skin Sens. Skin sensitization

BASF 3D Printing safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 10.02.2023
 Date previous version: 15.02.2022
 Date / First version: 05.08.2021
 Product: **Ultrafuse® ASA Black**

Version: 3.0
 Previous version: 2.0

(ID no. 11146758/SDS_GEN_EU/EN)

Date of print 02.02.2024

Aquatic Chronic	Hazardous to the aquatic environment - chronic
Eye Dam./Irrit.	Serious eye damage/eye irritation
Aquatic Acute	Hazardous to the aquatic environment - acute
Repr.	Reproductive toxicity
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.