

# Safety data sheet

Page: 1/14

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Ultrafuse® ASA Black**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: 3D Printing

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF 3D Printing Solutions B.V.  
Eerste Bokslootweg 17  
7821 AT Emmen, Netherlands

Contact address:

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

### 1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

No need for classification according to GHS criteria for this product.

## 2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

The product does not require a hazard warning label in accordance with GHS criteria.

## 2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

The product may cause burns, if handled in the melted state.

---

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Chemical nature

| Preparation based on: Polymer, additives

Hazardous ingredients (GHS)

| 2-(2H-Benzotriazol-2-yl)-p-cresol

| Content (W/W): > 0 % - < 1 %

| CAS Number: 2440-22-4

| EC-Number: 219-470-5

| REACH registration number: 01-2119583811-34

Skin Sens. 1B

Aquatic Chronic 1

M-factor chronic: 1

H317, H410

| Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

Content (W/W): > 0 % - < 1 %  
CAS Number: 52829-07-9  
EC-Number: 258-207-9  
REACH registration number: 01-2119537297-32

Eye Dam./Irrit. 1  
Aquatic Acute 1  
Aquatic Chronic 2  
Repr. 2 (fertility)  
M-factor acute: 1  
H318, H361f, H411, H400

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water. If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth immediately with water. Immediate medical attention required.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

Suitable extinguishing media:

water spray, foam, dry powder, carbon dioxide

### 5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

| Advice: The substances/groups of substances mentioned can be released in case of fire.

### **5.3. Advice for fire-fighters**

Special protective equipment:

| Wear a self-contained breathing apparatus.

Further information:

| Dust can form an explosive mixture with air. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## **SECTION 6: Accidental Release Measures**

| Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

### **6.1. Personal precautions, protective equipment and emergency procedures**

| No special precautions necessary.

### **6.2. Environmental precautions**

| Discharge into the environment must be avoided.

### **6.3. Methods and material for containment and cleaning up**

| For small amounts: Sweep/shovel up.

| For large amounts: Sweep/shovel up.

| Dispose of absorbed material in accordance with regulations. Avoid raising dust.

### **6.4. Reference to other sections**

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## **SECTION 7: Handling and Storage**

### **7.1. Precautions for safe handling**

| Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Protection against fire and explosion:

| The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

### **7.2. Conditions for safe storage, including any incompatibilities**

| Further information on storage conditions: Avoid deposition of dust. Avoid extreme heat.

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

Storage stability:

Protect against moisture.

### 7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

#### Components with occupational exposure limits

The substances mentioned are contained only in traces in the product. The release and quantity of the stated substance is dependent on the processing conditions.

#### 100-41-4: ethylbenzene

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

TWA value 441 mg/m<sup>3</sup> ; 100 ppm (WEL/EH 40 (UK))

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 884 mg/m<sup>3</sup> ; 200 ppm (OEL (EU))

indicative

TWA value 442 mg/m<sup>3</sup> ; 100 ppm (OEL (EU))

indicative

STEL value 552 mg/m<sup>3</sup> ; 125 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

#### 100-42-5: styrene

TWA value 430 mg/m<sup>3</sup> ; 100 ppm (WEL/EH 40 (UK))

STEL value 1,080 mg/m<sup>3</sup> ; 250 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

#### 107-13-1: acrylonitrile

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

TWA value 4.4 mg/m<sup>3</sup> ; 2 ppm (WEL/EH 40 (UK))

Skin Designation (Directive 2004/37/EC)

The substance can be absorbed through the skin.

TWA value 1 mg/m<sup>3</sup> ; 0.45 ppm (Directive 2004/37/EC)

The expiration date of this limit: 05 April 2026

STEL value 4 mg/m<sup>3</sup> (Directive 2004/37/EC)

STEL value 1.8 ppm (Directive 2004/37/EC)

#### 141-32-2: n-butyl acrylate

TWA value 5 mg/m<sup>3</sup> ; 1 ppm (WEL/EH 40 (UK))

STEL value 53 mg/m<sup>3</sup> ; 10 ppm (OEL (EU))

indicative

TWA value 11 mg/m<sup>3</sup> ; 2 ppm (OEL (EU))

indicative

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

STEL value 26 mg/m<sup>3</sup> ; 5 ppm (WEL/EH 40 (UK))  
Ceiling limit value/factor: 15 min  
8002-74-2: Paraffin waxes and Hydrocarbon waxes  
TWA value 2 mg/m<sup>3</sup> (WEL/EH 40 (UK)), fumes/smoke  
STEL value 6 mg/m<sup>3</sup> (WEL/EH 40 (UK)), fumes/smoke  
Ceiling limit value/factor: 15 min

## 8.2. Exposure controls

### Appropriate engineering controls

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

### Personal protective equipment

#### Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

#### Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

#### Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

#### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

### General safety and hygiene measures

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift. When using, do not eat, drink or smoke.

---

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Form:	filament
Colour:	black
Odour:	odourless

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

Odour threshold:	not applicable, odour not perceivable
pH value:	not applicable, substance/mixture is non-soluble (in water)
Melting point:	> 150 °C
Boiling point:	not applicable
Flash point:	not applicable, the product is a solid
Evaporation rate:	The product is a non-volatile solid.
Flammability:	Not a flammable solid according to UN transport regulations division 4.1 and GHS chapter 2.7.
Lower explosion limit:	For solids not relevant for classification and labelling.
Upper explosion limit:	For solids not relevant for classification and labelling.
Ignition temperature:	not applicable
Vapour pressure:	not determined
Density:	1.07 g/cm <sup>3</sup> (20 °C)
Relative density:	1.07 (20 °C)
Relative vapour density (air):	The product is a non-volatile solid.
Solubility in water:	insoluble
Partitioning coefficient n-octanol/water (log K <sub>ow</sub> ):	not applicable for mixtures
Self ignition:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated. Prolonged thermal loading can result in products of degradation being given off.
Explosion hazard:	not explosive
Fire promoting properties:	not fire-propagating

## 9.2. Other information

Self heating ability:	It is not a substance capable of spontaneous heating.
-----------------------	---

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

| No hazardous reactions if stored and handled as prescribed/indicated.

| Corrosion to metals: No corrosive effect on metal.

### 10.2. Chemical stability

| The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

| No hazardous reactions when stored and handled according to instructions.

### 10.4. Conditions to avoid

| Temperature: > 300 °C

| Prolonged exposure to elevated temperatures may result in exothermic decomposition accompanied by a pressure build-up in sealed containers. Avoid all sources of ignition: heat, sparks, open flame.

### 10.5. Incompatible materials

Substances to avoid:

| oxidizing agents

### 10.6. Hazardous decomposition products

| Hazardous decomposition products:

| Prolonged thermal loading can result in products of degradation being given off., monomers, gases/vapours, oxides, hydrocarbons, cyclic low molecular weight oligomers

## SECTION 11: Toxicological Information

### 11.1. Information on toxicological effects

#### Acute toxicity

Assessment of acute toxicity:

| Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Contact with molten product may cause thermal burns.

Experimental/calculated data:

| (oral): No applicable information available.

| (by inhalation): The inhalation of dusts represents a potential acute hazard.

| (dermal): No applicable information available.

#### Irritation

Assessment of irritating effects:

| Not irritating to eyes and skin. May cause mechanical irritation.



BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

#### Respiratory/Skin sensitization

Assessment of sensitization:

| Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Assessment of mutagenicity:

| Based on available data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity:

| Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

#### Developmental toxicity

Assessment of teratogenicity:

| Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

| Based on available data, the classification criteria are not met.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

| Based on available data, the classification criteria are not met.

#### Aspiration hazard

| not applicable

#### Other relevant toxicity information

The product has been assessed on the basis of the components' available data. To some extent data gaps exist for individual components. According to our present knowledge and experience dangers which are not covered by the current labeling are not to be expected.

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

---

## SECTION 12: Ecological Information

### 12.1. Toxicity

Assessment of aquatic toxicity:

Based on available data, the classification criteria are not met. At the present state of knowledge, no negative ecological effects are expected.

### 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

No data available concerning biodegradation and elimination.

### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

The product has not been tested.

### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Adsorption to solid soil phase is expected.

### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria.

### 12.6. Other adverse effects

The product does not contain substances that are listed in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

### 12.7. Additional information

Add. remarks environm. fate & pathway:

Due to the consistency of the product, dispersion into the environment is impossible. Therefore no negative effects on the environment may be anticipated based on the present state of knowledge.

Other ecotoxicological advice:

The product has been assessed on the basis of the components' available data. To some extent data gaps exist for individual components. According to our present knowledge and experience dangers which are not covered by the current labeling are not to be expected.

---

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Dispose of in accordance with national, state and local regulations.  
Contact specialized companies about recycling.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.  
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## SECTION 14: Transport Information

### Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

### Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

#### Transport in inland waterway vessel

Not evaluated

### **Sea transport**

#### IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

### **Air transport**

#### IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

---

### **SECTION 15: Regulatory Information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: no

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

#### **15.2. Chemical Safety Assessment**

Product is not classified as hazardous.

Chemical Safety Assessment not required

---

### **SECTION 16: Other Information**

Any other intended applications should be discussed with the manufacturer.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Sens.

Skin sensitization

Aquatic Chronic

Hazardous to the aquatic environment - chronic

Eye Dam./Irrit.

Serious eye damage/eye irritation

BASF 3D Printing Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.12.2022

Version: 3.0

Date previous version: 01.03.2022

Previous version: 2.0

Date / First version: 06.08.2021

Product: **Ultrafuse® ASA Black**

(ID no. 11146758/SDS\_GEN\_GB/EN)

Date of print 02.02.2024

Aquatic Acute	Hazardous to the aquatic environment - acute
Repr.	Reproductive toxicity
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.