

Helaian Data Keselamatan

Safety data sheet

Mukasurat (Page): 1/18

BASF 3D Printing Helaian Data Keselamatan (BASF 3D Printing Safety data sheet)

Tarikh / Disemak (Date / Revised): 12.07.2023

Versi (Version): 1.0

Produk (Product): **Ultrafuse® PLA Tough Natural**

(1106972/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 13.07.2023

1. Pengenalan bahan kimia dan pembekal

Ultrafuse® PLA Tough Natural

Penggunaan bahan kimia yang disyorkan dan sekatan penggunaan:

Cadangan penggunaan: Pencetakan 3D

Syarikat:

BASF 3D Printing Solutions B.V.

Eerste Bokslootweg 17

7821 AT Emmen, Netherlands

Alamat untuk hubungan:

BASF (Malaysia) Sdn Bhd

Lot 19.02 Level 19, 1 Powerhouse

No 1 Persiaran Bandar Utama

47800 Petaling Jaya

Selangor D.E, MALAYSIA

Nombor Telefon: +60 3 7612 1888

Nombor Telefax: +60 3 7612 1777

Maklumat kecemasan:

Nombor Kecemasan Kebangsaan

+603 7612 1999

Nombor Kecemasan Antarabangsa:

Nombor Telefon: +49 180 2273-112

2. Pengenalan Bahaya

Pengelasan bahan dan campuran:

Tidak memerlukan pengelasan menurut kriteria GHS untuk produk ini.

Unsur label dan pernyataan berjaga-jaga:

Produk tidak memerlukan label amaran bahaya menurut kriteria GHS .

Bahaya lain yang tidak menyebabkan pengelasan:

Produk boleh menyebabkan luka terbakar jika dikendalikan dalam keadaan lebur.

3. Komposisi dan Maklumat Mengenai Ramuan Bahan Kimia

Kedadaan kimia

Sediaan berdasarkan: Polimer, bahan tambah

Tiada bahaya khusus yang diketahui.

4. Langkah-Langkah Pertolongan Cemas

Nasihat am:

Tanggalkan pakaian yang tercemar.

Jika tersedut:

Alihkan mangsa ke kawasan berudara bersih dan pastikan mangsa dalam keadaan tenang. Jika gejala berterusan, dapatkan rawatan perubatan.

Apabila terkena kulit:

Basuh bersih-bersih dengan sabun dan air. Jika berlaku kerengsaan, segera dapatkan rawatan perubatan. Luka terbakar disebabkan oleh bahan lebur memerlukan rawatan hospital.

Apabila terkena mata:

Basuh mata yang terkena produk selama sekurang-kurangnya 15 minit di bawah aliran air sambil membuka mata. Jika berlaku kerengsaan, segera dapatkan rawatan perubatan.

Apabila tertelan:

Segera basuh mulut dengan air. Rawatan perubatan segera diperlukan.

Nota kepada doktor:

Gejala: Simptom dan/atau kesan tidak diketahui setakat ini

Nota kepada doktor:

Bahaya: Tiada bahaya dijangka dengan penggunaan yang disyorkan dan pengendalian yang sesuai.

Rawatan: Rawat mengikut gejala (nyahcemar, fungsi utama), tiada penawar khusus diketahui.

5. Langkah-Langkah Pemadaman Kebakaran

Bahan pemadam yang sesuai:

semburan air, busa, serbuk kering, karbon dioksida

Bahaya tertentu:

karbon oksida

Bahan/kumpulan bahan yang dinyatakan boleh dibebaskan jika berlaku kebakaran.

Peralatan perlindungan khusus:

Gunakan alat pernafasan serba lengkap.

Maklumat lanjut:

Debu boleh membentuk campuran mudah meletup di udara. Lupuskan sisa kebakaran dan air pemadam api yang tercemar menurut peraturan rasmi.

6. Langkah-Langkah Pelepasan Tidak Sengaja

Perlindungan diri, kelengkapan pelindung dan tatacara kecemasan:
Tiada langkah berjaga-jaga yang khusus diperlukan.

Langkah berjaga-jaga untuk alam sekitar:
Pelepasan ke alam sekitar mestilah dielakkan.

Kaedah pembersihan atau penyerapan:
Bagi sejumlah kecil: Sapu/sodok.
Bagi sejumlah besar: Sapu/sodok.
Lupuskan bahan yang diserap mengikut peraturan. Elakkan pertambahan debu.

Maklumat tambahan: Elakkan penyebaran habuk ke udara (iaitu bersihkan permukaan berhabuk dengan udara termampat) Elakkan pembentukan dan pengumpulan debu - bahaya letupan debu. Habuk yang mencukupi kepekataannya boleh menyebabkan campuran mudah meletup dalam udara. Kendalikan bagi mengurangkan pembentukan habuk dan hapuskan api terdedah serta sumber penyalan lain.

7. Pengendalian dan Penyimpanan

Pengendalian

Elakkan daripada tersedut debu/kabus/wap. Pastikan pengalihudaraan yang mencukupi. Sediakan ekzos pengalihan udara yang sesuai pada proses pengeringan dan pada persekitaran bahagian keluar cairan pada mesin pemprosesan. Jauhkan dari sumber pencucuhan - Dilarang merokok. Ambil langkah berjaga-jaga terhadap luahan statik. Cegah pembentukan dan pengumpulan debu.

Perlindungan terhadap kebakaran dan letupan:
Produk ini tidak menyebabkan kebakaran merebak, tidak mudah terbakar dan tidak mudah meletup. Elakkan pembentukan debu. Habuk yang mencukupi kepekataannya boleh menyebabkan campuran mudah meletup dalam udara. Kendalikan bagi mengurangkan pembentukan habuk dan hapuskan api terdedah serta sumber penyalan lain.

Penyimpanan

Maklumat lanjut tentang keadaan penyimpanan: Elakkan pengumpulan debu. Jauhkan dari haba yang terlalu panas.

Kestabilan penyimpanan:
Lindungi daripada lembapan.

8. Kawalan pendedahan dan perlindungan diri

Komponen dengan parameter kawalan tempat kerja

Tiada had pendedahan pekerjaan tertentu yang diketahui.

Peralatan perlindungan peribadi

Perlindungan pernafasan:

Perlindungan pernafasan jika aerosol/debu boleh sedut terbentuk. Pakai perlindungan pernafasan jika pengalihudaraan tidak mencukupi. Penapis zarah jenis kecekapan sederhana untuk zarah pepejal dan cecair (misalnya EN 143 atau 149, Jenis P2 atau FFP2)

Perlindungan tangan:

Gunakan sarung tangan pelindung haba tambahan apabila mengendalikan jisim lebur panas (EN 407), contohnya tekstil atau kulit.

Perlindungan mata:

Kaca mata keselamatan dengan pelindung sisi (gogal berbingkai) (contohnya EN 166)

Perlindungan badan:

Perlindungan badan mesti dipilih bergantung kepada aktiviti dan pendedahan, contohnya apron, kasut perlindungan, pakaian perlindungan bahan kimia (Berdasarkan DIN-EN 465)

Langkah kebersihan dan keselamatan am:

Pakai pakaian pelindung untuk mengelakkan terkena produk semasa pemprosesan mekanikal dan/atau keadaan lebur panas. Simpan pakaian kerja secara berasingan. Tangan dan/atau muka hendaklah dibasuh sebelum rehat dan setelah tamat waktu bekerja. Jangan makan, minum atau merokok semasa menggunakannya.

9. Sifat Fizikal dan Kimia

Bentuk:	Filamen
Warna:	kuning air ke coklat cair
Bau:	tidak berbau
Ambang bau:	tidak berkenaan, bau tidak dapat dikesan

nilai pH:	tidak ditentukan
-----------	------------------

takat lebur:	177 °C
takat didih:	tidak ditentukan

Takat kilat:	tidak ditentukan
--------------	------------------

Tahap penyejatan:	Produk ini adalah pepejal tidak meruap
-------------------	--

Kemudahbakaran (pepejal/gas):	tidak ditentukan
-------------------------------	------------------

Had letupan bawah:	Tidak berkaitan untuk pengelasan dan pelabelan bagi pepejal.
--------------------	--

Had letupan atas:	Tidak berkaitan untuk pengelasan dan pelabelan bagi pepejal.
Suhu pencucuhan:	tidak ditentukan
Penguraian terma:	> 230 °C
pencucuhan sendiri:	Tidak swacucuh.
Kebolehan swapemanasan sendiri:	Ia bukanlah bahan yang mampu pemanasan spontan.
Bahaya letupan:	tidak mudah meletup
Sifat yang menggalakkan kebakaran:	tidak merebakkan api
Tekanan Wap:	Produk ini adalah pepejal tidak meruap
Kepekatan:	1.22 g/cm ³ (20 °C, 1,013 hPa)
Ketumpatan pukal:	tidak ditentukan
Ketumpatan wap relatif (udara):	Produk ini adalah pepejal tidak meruap
Keterlarutan dalam air:	tidak ditentukan
Pekali petakan n-oktanol/air (log Pow):	tidak ditentukan
Kelikatan, dinamik:	tidak boleh digunakan, produk adalah pepejal
Kelikatan, kinematik:	tidak boleh digunakan, produk adalah pepejal

10. Kestabilan dan Kereaktifan

Keadaan yang perlu dielakkan:

Suhu: > 230 °C

Jauhkan dari semua sumber pencucuhan: haba, percikan api, nyalaan terbuka.

Penguraian terma: > 230 °C

Bahan yang perlu dielakkan:

agen pengoksida, bes kuat

Kakisan kepada logam: Tiada kesan mengakis pada logam

Tindak balas berbahaya:
Akumulasi debu halus boleh menimbulkan risiko letupan debu dengan adanya udara.

Produk penguraian terma yang mungkin:
aldehid, karbon oksida, Gas/wap toksik

Kereaktifan:
Tiada produk penguraian yang berbahaya jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Kestabilan kimia:
Produk adalah stabil jika disimpan dan dikendalikan sebagaimana

11. Maklumat Toksikologi

Ketoksikan akut

Penilaian ketoksikan akut:
Tidak toksik selepas sekali ditelan. Tidak toksik jika tersedut. Tidak toksik selepas sekali terkena kulit
Terkena produk lebur boleh menyebabkan luka terbakar terma.

Data eksperimen/dikira:
LD50 tikus (melalui mulut): > 5,000 mg/kg

(melalui penyedutan):Penyedutan habuk berkemungkinan menyebabkan bahaya akut.

LD50 arnab (dermal): > 2,000 mg/kg

Kerengsaan

Penilaian kesan merengsa:
Tidak merengsa kepada mata dan kulit. boleh menyebabkan kerengsaan mekanikal

Pemekaan pernafasan/kulit

Penilaian pemekaan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Kemutagenan sel germa

Penilaian kemutagenan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Kekarsinogenan

Penilaian kekarsinogenan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan pembiakan

Penilaian ketoksikan pembiakan:

Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan perkembangan

Penilaian keteratogenan:

Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan khusus organ sasaran (sekali pendedahan):

Penilaian sekali STOT:

Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan dos berulang dan Ketoksikan organ sasaran tertentu (pendedahan berulang)

Penilaian ketoksikan dos berulang:

Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Bahaya penyedutan

Tidak boleh digunakan

12. Maklumat Ekologi

Keekotoksikan

Penilaian ketoksikan akuatik:

Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi. Setakat yang diketahui sehingga ini, kesan ekologi yang negatif tidak dijangka.

Mobiliti

Penilaian pengangkutan di antara bahagian di persekitaran:

Penjerapan kepada fasa tanah pejal dijangka

Keterusan dan boleh keterdegradasikan

Penilaian biodegradasi dan penyingkiran (H₂O):

Tiada data diperolehi tentang biodegradasi dan penyingkiran.

Potensi Biotumpukan

Penilaian potensi bioakumulasi:

Produk belum diuji.

Maklumat tambahan

Perhatian tambahan bagi nasib pada alam sekitar & laluan:

Disebabkan ketekalan produk, penyebaran ke persekitaran adalah mustahil. Oleh itu kesan negatif kepada alam sekitar mungkin tidak dijangka setakat yang diketahui sehingga kini.

13. Maklumat Pelupusan

Lupuskan mengikut peraturan kebangsaan, negeri dan tempatan.
Hubungi syarikat yang khusus berkenaan kitar semula.

Pembungkusan tercemar:

Lupuskan mengikut peraturan kebangsaan, negeri dan tempatan.

Bungkusan yang tercemar hendaklah dikosongkan sejauh yang boleh dan dilupuskan dengan cara yang sama melupuskan bahan/produk.

14. Maklumat Pengangkutan

Pengangkutan domestik:

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan laut

IMDG

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan udara

IATA/ICAO

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan secara pukal menurut Lampiran II MARPOL dan IBC

Peraturan: Tidak dinilai

Penghantaran yang diluluskan: Tidak dinilai

Nama pencemaran: Tidak dinilai

Kategori pencemaran: Tidak dinilai

Jenis Kapal: Tidak dinilai

15. Maklumat Pengawalseliaan

Peraturan-Peraturan Keselamatan dan Kesihatan Pekerjaan (Pengelasan, Pelabelan dan Helaian Data Keselamatan Bahan kimia Berbahaya) 2013

Akta OSHA 1994 dan peraturan berkaitan

Akta Kualiti Alam Sekeliling 1974

Maklumat tentang peraturan-peraturan tidak meliputi kesemuanya. Peraturan-peraturan lain mungkin dikenakan kepada bahan ini.

Peraturan lain

Jika maklumat peraturan lain yang berkenaan tidak dinyatakan dibahagian lain didalam risalah data keselamatan ini, ianya akan dinyatakan bahagian ini.

16. Maklumat lain

Tarikh Penyediaan / Tarikh Penyemakan: 12.07.2023

Sumber Maklumat dan Rujukan :

SDS ini disediakan dengan menggunakan data dan maklumat tersimpan di dalam sistem berasaskan IT dalaman kami dan dibekalkan oleh pembekal perkhidmatan syarikat kami.

Singkatan Petunjuk:

ATE - Anggaran Ketoksikan Akut

GHS - Sistem Terharmoni Global

IATA / ICAO - Persatuan Pengangkutan Udara Antarabangsa / Organisasi Penerbangan Awam Antarabangsa

IBC - Kontena Pukul Pertengahan

IMDG - Barangan Merbahaya Kelautan Antarabangsa

LC - Kepekatan Maut

LD - Dos Maut

OECD - Organisasi Untuk Kerjasama dan Pembangunan Ekonomi

OEL - Had Pendedahan Pekerjaan

OSHA - Akta Keselamatan dan Kesihatan Pekerjaan

STOT - Ketoksikan Organ Sasaran Khusus

Sebarang tujuan penggunaan lain hendaklah dibincangkan dengan pengeluar.

Garis menegak pada margin sebelah kiri tangan menunjukkan pindaan dari versi sebelumnya.

Data yang terdapat dalam risalah data keselamatan ini adalah berdasarkan pengetahuan dan pengalaman kami, dan menerangkan tentang produk yang berkaitan dengan keperluan keselamatan sahaja. Data tidak menyatakan ciri produk (spesifikasi produk). Data dalam risalah data keselamatan ini juga tidak menyatakan apa-apa ciri khusus atau kesesuaian produk yang dipersetujui untuk apa-apa tujuan tertentu. Penerima produk bertanggungjawab untuk memastikan bahawa apa-apa hak pemilikan serta undang-undang dan perundangan sedia ada dipatuhi.

1. Identification of the chemical and of the supplier

Ultrafuse® PLA Tough Natural

Recommended use of the chemical and restriction on use:

Recommended use: 3D Printing

Company:

BASF 3D Printing Solutions B.V.

Eerste Bokslootweg 17

7821 AT Emmen, Netherlands

Contact address:

BASF (Malaysia) Sdn Bhd

Lot 19.02 Level 19, 1 Powerhouse

No 1 Persiaran Bandar Utama

47800 Petaling Jaya

Selangor D.E, MALAYSIA

Telephone: +60 3 7612 1888

Telefax number: +60 3 7612 1777

Emergency information:

National emergency number:

+603 7612 1999

International emergency number:

Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

No need for classification according to GHS criteria for this product.

Label elements and precautionary statement:

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards which do not result in classification:

The product may cause burns, if handled in the melted state.

3. Composition/information on ingredients

Chemical nature

Preparation based on: Polymer, additives

No particular hazards known.

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water. If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth immediately with water. Immediate medical attention required.

Note to physician:

Symptoms: (Further) symptoms and / or effects are not known so far

Note to physician:

Hazards: No hazard is expected under intended use and appropriate handling.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

water spray, foam, dry powder, carbon dioxide

Specific hazards:

carbon oxides

The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dust can form an explosive mixture with air. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

No special precautions necessary.

Environmental precautions:

Discharge into the environment must be avoided.

Methods for cleaning up or taking up:

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Additional information: Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

7. Handling and Storage

Handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Protection against fire and explosion:

The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Storage

Further information on storage conditions: Avoid deposition of dust. Avoid extreme heat.

Storage stability:

Protect against moisture.

8. Exposure controls and personal protection

Components with occupational exposure limits

No substance specific occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift. When using, do not eat, drink or smoke.

9. Physical and Chemical Properties

Form:	filament
Colour:	beige to light brown
Odour:	odourless
Odour threshold:	not applicable, odour not perceivable

pH value:	not determined
-----------	----------------

Melting point:	177 °C
Boiling point:	not determined

Flash point:	not determined
--------------	----------------

Evaporation rate:	The product is a non-volatile solid.
-------------------	--------------------------------------

Flammability (solid/gas):	not determined
Lower explosion limit:	

For solids not relevant for classification and labelling.

Upper explosion limit:	
	For solids not relevant for classification and labelling.

Ignition temperature:	not determined
-----------------------	----------------

Thermal decomposition:	> 230 °C
Self ignition:	not self-igniting

Self heating ability:	It is not a substance capable of spontaneous heating.
-----------------------	---

Explosion hazard:	not explosive
Fire promoting properties:	not fire-propagating

Vapour pressure:	The product is a non-volatile solid.
------------------	--------------------------------------

Density:	1.22 g/cm ³ (20 °C, 1,013 hPa)
Bulk density:	not determined
Relative vapour density (air):	The product is a non-volatile solid.
Solubility in water:	not determined
Partitioning coefficient n-octanol/water (log Pow):	not determined
Viscosity, dynamic:	not applicable, the product is a solid
Viscosity, kinematic:	not applicable, the product is a solid

10. Stability and Reactivity

Conditions to avoid:
Temperature: > 230 °C
Avoid all sources of ignition: heat, sparks, open flame.

Thermal decomposition: > 230 °C

Substances to avoid:
oxidizing agents, strong bases

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:
Accumulation of fine dust may entail the risk of a dust explosion in the presence of air.

Possible thermal decomposition products:
aldehydes, carbon oxides, toxic gases/vapours

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:
Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Contact with molten product may cause thermal burns.

Experimental/calculated data:

LD50 rat (oral): > 5,000 mg/kg

(by inhalation): The inhalation of dusts represents a potential acute hazard.

LD50 rabbit (dermal): > 2,000 mg/kg

Irritation

Assessment of irritating effects:

Not irritating to eyes and skin. May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure):

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

not applicable

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

Based on available data, the classification criteria are not met. At the present state of knowledge, no negative ecological effects are expected.

Mobility

Assessment transport between environmental compartments:

Adsorption to solid soil phase is expected.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

No data available concerning biodegradation and elimination.

Bioaccumulation potential

Assessment bioaccumulation potential:

The product has not been tested.

Additional information

Add. remarks environm. fate & pathway:

Due to the consistency of the product, dispersion into the environment is impossible. Therefore no negative effects on the environment may be anticipated based on the present state of knowledge.

13. Disposal Information

Dispose of in accordance with national, state and local regulations.

Contact specialized companies about recycling.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transportation Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

15. Regulatory Information

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

OSHA 1994 and relevant regulations

Environmental Quality Act, 1974

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Date of Preparation / Date of Revision: 12.07.2023

Information Source and References:

This SDS is prepared using data and information saved in our internal IT-based system and supplied by our company's service providers.

Key Abbreviations:

ATE - Acute Toxicity Estimates

GHS - Globally Harmonized System

IATA / ICAO - International Air Transport Association / International Civil Aviation Organization

IBC - Intermediate Bulk Container

IMDG - International Maritime Dangerous Goods

LC - Lethal Concentration

LD - Lethal Dose

OECD - Organisation for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OSHA - Occupational Safety and Health Act

STOT - Specific Target Organ Toxicity

Any other intended applications should be discussed with the manufacturer.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.