

# Safety data sheet

Page: 1/9

BASF 3D Printing Safety data sheet  
Date / Revised: 10.11.2020  
Product: **Ultrafuse® TPU 95A White**

Version: 1.0

(11137026/SDS\_GEN\_SG/EN)

Date of print 10.01.2023

## 1. Substance/preparation and manufacturer/supplier identification

### Ultrafuse® TPU 95A White

Recommended use: 3D Printing, for industrial use only

Manufacturer/supplier:

BASF 3D Printing Solutions B.V.  
Eerste Bokslootweg 17  
7821 AT Emmen, Netherlands  
Contact address:  
BASF SEA Pte Ltd  
7 Temasek Boulevard,  
#35-01 Suntec Tower One, 038987  
SINGAPORE  
Telephone: +65 6 337-0330  
Telefax number: +65 6 334-0330  
E-mail address: carlos.mandia@basf.com

Emergency information:

Singapore Emergency Toll-Free Number:  
Telephone: 1800-723-1361  
International emergency number:  
Telephone: +49 180 2273-112

## 2. Hazard identification

Classification of the substance and mixture:

No need for classification according to GHS criteria for this product.

Label elements and precautionary statement:

The product does not require a hazard warning label in accordance with GHS criteria.

BASF 3D Printing Safety data sheet  
Date / Revised: 10.11.2020  
Product: **Ultrafuse® TPU 95A White**

Version: 1.0

(11137026/SDS\_GEN\_SG/EN)

Date of print 10.01.2023

Other hazards which do not result in classification:  
No specific dangers known, if the regulations/notes for storage and handling are considered.

---

### 3. Composition/information on ingredients

#### Chemical nature

Polymer based on: polyurethane, stabilizing agents, additives

No particular hazards known.

---

### 4. First-Aid Measures

General advice:  
Remove contaminated clothing.

If inhaled:  
Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. If symptoms persist, seek medical advice.

On skin contact:  
Wash thoroughly with soap and water Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

On contact with eyes:  
In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:  
Keep patient calm, remove to fresh air. Immediate medical attention required.

Note to physician:  
Symptoms: (Further) symptoms and / or effects are not known so far  
Hazards: No hazard is expected under intended use and appropriate handling.  
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

### 5. Fire-Fighting Measures

Suitable extinguishing media:  
water spray, foam, dry powder

Specific hazards:  
carbon oxides  
The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:  
Wear a self-contained breathing apparatus.

Further information:  
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental Release Measures

Personal precautions:  
No special precautions necessary.

Environmental precautions:  
Discharge into the environment must be avoided.

Methods for cleaning up or taking up:  
For small amounts: Sweep/shovel up.  
For large amounts: Sweep/shovel up. Vacuum up spilled product.  
Reclaim for processing if possible. Ensure adequate ventilation.

---

## 7. Handling and Storage

### Handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Protection against fire and explosion:  
The product is not an oxidizer, not self-combustible and not explosive.

### Storage

Segregate from foods and animal feeds.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard, Polystyrene (PS)  
Further information on storage conditions: Avoid extreme heat. Protect against moisture.

Storage stability:  
Protect against moisture.

---

## 8. Exposure controls and personal protection

### Components with occupational exposure limits

Titanium dioxide, 13463-67-7;  
TWA value 10 mg/m<sup>3</sup> (ACGIHTLV)  
TWA value 10 mg/m<sup>3</sup> (OEL (SG))

#### Personal protective equipment

##### Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

##### Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

##### Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

##### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

##### General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

---

## 9. Physical and Chemical Properties

Form:	filament
Colour:	white
Odour:	odourless
Odour threshold:	not applicable

pH value:	not applicable
-----------	----------------

softening temperature:	> 120 °C
boiling temperature:	The product is a non-volatile solid.

Flash point:	not applicable
--------------	----------------

Evaporation rate:	The product is a non-volatile solid.
-------------------	--------------------------------------

Flammability (solid/gas):	Not a flammable solid according to UN transport regulations division 4.1 and GHS chapter 2.7. Based on the structure or composition there is no indication of flammability
---------------------------	---

Lower explosion limit:	For solids not relevant for classification and labelling.
------------------------	---

Upper explosion limit:	For solids not relevant for classification and labelling.
Ignition temperature:	> 400 °C
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.  > 230 °C Thermal decomposition above the indicated temperature is possible.  Prolonged thermal loading can result in products of degradation being given off.
Self ignition:	not self-igniting
Self heating ability:	It is not a substance capable of spontaneous heating according to UN transport regulations class 4.2.
Explosion hazard:	not explosive
Fire promoting properties:	not fire-propagating
Vapour pressure:	not applicable
Density:	approx. 1.1 - 1.2 g/cm <sup>3</sup> (20 °C)
Relative density:	approx. 1.1 - 1.2 (20 °C)
Bulk density:	500 - 700 kg/m <sup>3</sup> (20 °C)
Relative vapour density (air):	not applicable
Solubility in water:	insoluble
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Viscosity, dynamic:	not applicable

---

## 10. Stability and Reactivity

Conditions to avoid:  
No conditions to avoid anticipated.

Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Thermal decomposition:	> 230 °C

BASF 3D Printing Safety data sheet  
Date / Revised: 10.11.2020  
Product: **Ultrafuse® TPU 95A White**

Version: 1.0

(11137026/SDS\_GEN\_SG/EN)

Date of print 10.01.2023

Thermal decomposition above the indicated temperature is possible.

Thermal decomposition:

Prolonged thermal loading can result in products of degradation being given off.

Substances to avoid:  
oxidizing agents

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

No hazardous reactions when stored and handled according to instructions.

Thermal decomposition products:

Prolonged thermal loading can result in products of degradation being given off.

---

## 11. Toxicological Information

### Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

Experimental/calculated data:

(by inhalation): The inhalation of dusts represents a potential acute hazard.

(dermal): No applicable information available.

### Irritation

Assessment of irritating effects:

May cause slight irritation to the skin. May cause slight irritation to the eyes.

Experimental/calculated data:

Skin corrosion/irritation: May cause mechanical irritation.

Serious eye damage/irritation: May cause mechanical irritation.

### Respiratory/Skin sensitization

Assessment of sensitization:

The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Germ cell mutagenicity

Assessment of mutagenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## **Carcinogenicity**

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## **Reproductive toxicity**

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## **Developmental toxicity**

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## **Specific target organ toxicity (single exposure):**

Assessment of STOT single:

The available information is not sufficient for the evaluation of specific target organ toxicity.

## **Repeated dose toxicity and Specific target organ toxicity (repeated exposure)**

Assessment of repeated dose toxicity:

Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## **Aspiration hazard**

No aspiration hazard expected.

## **Other relevant toxicity information**

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

---

## **12. Ecological Information**

### **Ecotoxicity**

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

### **Mobility**

Assessment transport between environmental compartments:  
Due to the product characteristics the test is impossible.

### **Persistence and degradability**

Assessment biodegradation and elimination (H<sub>2</sub>O):  
Poorly biodegradable.

Elimination information:  
Poorly biodegradable.

### **Bioaccumulation potential**

Assessment bioaccumulation potential:  
Does not significantly accumulate in organisms.

### **Other adverse effects**

Adsorbable organically-bound halogen (AOX):  
This product contains no organically-bound halogen.

### **Additional information**

Other ecotoxicological advice:  
The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

---

## **13. Disposal Considerations**

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:  
Dispose of in accordance with national, state and local regulations.

---

## **14. Transport Information**

### **Domestic transport:**

Not classified as a dangerous good under transport regulations

### **Sea transport**

IMDG

Not classified as a dangerous good under transport regulations

### **Air transport**

IATA/ICAO



BASF 3D Printing Safety data sheet  
Date / Revised: 10.11.2020  
Product: **Ultrafuse® TPU 95A White**

Version: 1.0

(11137026/SDS\_GEN\_SG/EN)

Date of print 10.01.2023

Not classified as a dangerous good under transport regulations

---

## 15. Regulatory Information

### Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

---

## 16. Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.