

Safety data sheet

Page: 1/11

BASF 3D Printing Safety data sheet

Date / Revised: 20.07.2022

Product: **Ultrafuse Support Layer**

Version: 2.0

(11154042/SDS_GEN_NZ/EN)

Date of print): 10.01.2023

1. Substance/preparation and manufacturer/supplier identification

Product name:
Ultrafuse Support Layer

Recommended use: 3D Printing

Manufacturer/supplier:

BASF 3D Printing Solutions B.V.

Eerste Bokslootweg 17

7821 AT Emmen, Netherlands

Contact address:

BASF New Zealand Ltd.

5E City Works Depot

77 Cook Street

Auckland Central, Auckland 1010

NEW ZEALAND

Telephone: +64 9 255-4300

Telefax number: +64 9 255-4307

Emergency information:

National Poisons Centre: 0800 764 766

BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)

BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

2. Hazard identification

Classification of the substance and mixture:

Hazardous to the aquatic environment - chronic: Cat.3

Label elements and precautionary statement:

Hazard Statement:

H412

Harmful to aquatic life with long lasting effects.

BASF 3D Printing Safety data sheet
 Date / Revised: 20.07.2022
 Product: **Ultrafuse Support Layer**

Version: 2.0

(11154042/SDS_GEN_NZ/EN)

Date of print: 10.01.2023

Precautionary Statements (Prevention):

P273 Avoid release to the environment.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Upon mechanical treatment like e.g. cutting, grinding and/or polishing the product can release hazardous substances.

Upon thermal and/or chemical treatment the product can release hazardous substances.

Fine dust produced by abrasion can form explosive mixtures with air.

3. Composition/information on ingredients

Chemical nature

Substance nature: mixture

polymer blend based on: metal oxides, encapsulated, in a polymer matrix

Hazardous ingredients

| ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)

Content (W/W): $\geq 0.2\%$ - $< 0.3\%$ Aquatic Chronic: Cat. 1
 CAS Number: 36443-68-2 M-factor chronic: 10

formaldehyde

Content (W/W): $> 0\%$ - $< 0.1\%$ Flam. Liq.: Cat. 4
 CAS Number: 50-00-0 Acute Tox.: Cat. 2 (Inhalation - vapour)
 Acute Tox.: Cat. 3 (oral)
 Acute Tox.: Cat. 3 (dermal)
 Skin Corr./Irrit.: Cat. 1B
 Eye Dam./Irrit.: Cat. 1
 Skin Sens.: Cat. 1A
 Carc.: Cat. 1B
 Aquatic Acute: Cat. 2

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice.

BASF 3D Printing Safety data sheet
Date / Revised: 20.07.2022
Product: **Ultrafuse Support Layer**

Version: 2.0

(11154042/SDS_GEN_NZ/EN)

Date of print): 10.01.2023

On skin contact:

Wash thoroughly with soap and water. If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. Seek medical attention.

Note to physician:

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

water spray, foam, dry powder, carbon dioxide

Additional information:

Water spray for suppression (heat dissipation) of incipient fires as long as the product has not yet ignited.

Specific hazards:

formaldehyde, carbon oxides

The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Handle in accordance with good industrial hygiene and safety practice.

Environmental precautions:

Discharge into the environment must be avoided.

Methods for cleaning up or taking up:
For small amounts: Sweep/shovel up.
For large amounts: Sweep/shovel up.
Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Additional information: Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

7. Handling and Storage

Handling

Avoid inhalation of dusts/mists/vapours. Provide good ventilation of working area (local exhaust ventilation if necessary). Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Further information is given in the user guidelines for the product.

Protection against fire and explosion:

The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Accumulation of fine dust may entail the risk of a dust explosion in the presence of air.

Storage

Segregate from acids.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Avoid deposition of dust. Avoid extreme heat.

Storage stability:

Protect against moisture.

The packed product is not damaged by low temperatures or by frost.

Protect from temperatures above: 160 °C

Changes in the properties of the product may occur if substance/product is stored above indicated temperature for extended periods of time.

8. Exposure controls and personal protection

Components with occupational exposure limits

aluminium oxide, 1344-28-1;

TWA value 1 mg/m³ (ACGIHTLV), Respirable fraction

TWA value 10 mg/m³ (OEL (NZ))

TWA value 10 mg/m³ (ACGIHTLV), Inhalable particles

TWA value 3 mg/m³ (ACGIHTLV), Respirable particles

The release and quantity of the stated substance is dependent on the processing conditions.

formaldehyde, 50-00-0;

STEL value 0.3 ppm (ACGIHTLV)

TWA value 0.1 ppm (ACGIHTLV)

TWA value 0.3 ppm (OEL (NZ))

This is an interim WES and WorkSafe considers it may not be protective for all workers. As such, caution should be applied in using the WES for health risk assessment. WorkSafe intends to lower the WES in the future for

Formaldehyde: Interim WES-TWA 0.3ppm and WES-STEL 0.6ppm. Proposed to change WES-TWA to 0.1ppm and WES-STEL to 0.3ppm in Nov 2022.

STEL value 0.6 ppm (OEL (NZ))

This is an interim WES and WorkSafe considers it may not be protective for all workers. As such, caution should be applied in using the WES for health risk assessment. WorkSafe intends to lower the WES in the future for

Formaldehyde: Interim WES-TWA 0.3ppm and WES-STEL 0.6ppm. Proposed to change WES-TWA to 0.1ppm and WES-STEL to 0.3ppm in Nov 2022.

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Wearing of closed work clothing is recommended. Ensure adequate ventilation. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	filament
Colour:	white
Odour:	odourless
Odour threshold:	not applicable, odour not perceivable

BASF 3D Printing Safety data sheet

Date / Revised: 20.07.2022

Product: **Ultrafuse Support Layer**

Version: 2.0

(11154042/SDS_GEN_NZ/EN)

Date of print): 10.01.2023

pH value:	not applicable, substance/mixture is non-soluble (in water)	
Melting point:	163 °C	
Boiling point:	not applicable	
Flash point:	not applicable, the product is a solid	
Evaporation rate:	The product is a non-volatile solid.	
Flammability (solid/gas):	not highly flammable	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Ignition temperature:	not applicable	
Thermal decomposition:	> 200 °C Thermal decomposition above the indicated temperature is possible.	
Self ignition:	not self-igniting	
Self heating ability:	It is not a substance capable of spontaneous heating.	
Explosion hazard:	Product is not explosive, however a dust explosion could result from an air / dust mixture.	
Fire promoting properties:	not fire-propagating	
Radioactivity:		not radioactive for transport purposes
Vapour pressure:	not determined	
Bulk density:	570 kg/m ³	(DIN EN ISO 60)
Relative vapour density (air):	The product is a non-volatile solid.	
Solubility in water:	insoluble	
Hygroscopy:	Non-hygroscopic	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Viscosity, kinematic:	not applicable, the product is a solid	

10. Stability and Reactivity

Conditions to avoid:

Avoid all sources of ignition: heat, sparks, open flame. Avoid prolonged exposure to extreme heat.
Avoid dust formation.

Thermal decomposition: > 200 °C
Thermal decomposition above the indicated temperature is possible.

Substances to avoid:

oxidizing agents, inorganic acids, plastics containing halogenated flame retardants

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

Strong exothermic reaction with acids. May decompose violently.
The product is stable if stored and handled as prescribed/indicated.

Possible thermal decomposition products:

formaldehyde, carbon monoxide

At prolonged and/or strong thermal stressing above the decomposition temperature dangerous decomposition products can be formed.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated. depolymerizes at elevated temperatures

11. Toxicological Information

Routes of exposure

Assessment of acute toxicity

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Contact with molten product may cause thermal burns.

Symptoms

(Further) symptoms and / or effects are not known so far

Irritation

Assessment of irritating effects:

May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration hazard

not applicable

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Mobility

Assessment transport between environmental compartments:

Adsorption to solid soil phase is possible.

Bioaccumulation potential

Assessment bioaccumulation potential:

The product has not been tested.

Bioaccumulation potential:

The product has not been tested. Because of the product's consistency and low water solubility, bioavailability is improbable.

Additional information

Add. remarks environm. fate & pathway:

The product has not been tested. The statements on environmental fate and pathway have been derived from the properties of the individual components.

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Considerations

Dispose of in accordance with national, state and local regulations.

Contact specialized companies about recycling.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Domestic transport:

UN number or ID number	Not classified as a dangerous good under transport regulations
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number	Not applicable
Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

15. Regulatory Information**Other regulations**

A certified handler is not required for the handling of this substance.
Tracking requirements do not apply to this substance.

HSNO Approval Number HSR002503

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017

16. Other Information

Any other intended applications should be discussed with the manufacturer.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF 3D Printing Safety data sheet

Date / Revised: 20.07.2022

Version: 2.0

Product: **Ultrafuse Support Layer**

(11154042/SDS_GEN_NZ/EN)

Date of print): 10.01.2023

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.