

Safety data sheet

Page: 1/9

BASF 3D Printing Safety data sheet

Date / Revised: 03.09.2020

Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

1. Substance/preparation and manufacturer/supplier identification

Ultrafuse® PET Grey

Recommended use: 3D Printing, for industrial use only

Manufacturer/supplier:

BASF 3D Printing Solutions B.V.

Eerste Bokslootweg 17

7821 AT Emmen, Netherlands

Contact address:

BASF Philippines, Inc.

Upper Penthouse CTP ASEAN Tower

Asean Drive, Spectrum District

Filinvest Corporate City, Alabang,

Muntinlupa City, 1781, Metro Manila

PHILIPPINES

Telephone: +63 2 811-8000

E-mail address: psr.ph@basf.com

Emergency information:

National emergency number:

+63 2 8831 5576

International emergency number:

Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

No need for classification according to GHS criteria for this product.

Label elements and precautionary statement:

BASF 3D Printing Safety data sheet
Date / Revised: 03.09.2020
Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards which do not result in classification:

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition/information on ingredients

Chemical nature

Polymer

No particular hazards known.

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Keep patient calm, remove to fresh air. Immediate medical attention required.

Note to physician:

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

water spray, foam, dry powder

Specific hazards:

carbon oxides

The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:

Wear a self-contained breathing apparatus.

BASF 3D Printing Safety data sheet
Date / Revised: 03.09.2020
Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

No special precautions necessary.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up. Vacuum up spilled product.

Reclaim for processing if possible. Ensure adequate ventilation. Avoid raising dust.

Additional information: Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

7. Handling and Storage

Handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Protection against fire and explosion:

The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Storage

Storage stability:

Protect against moisture.

8. Exposure controls and personal protection

Components with occupational exposure limits

No occupational exposure limits known.

BASF 3D Printing Safety data sheet
Date / Revised: 03.09.2020
Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	filament
Colour:	grey
Odour:	odourless
Odour threshold:	not applicable

pH value:	not applicable
-----------	----------------

Melting point:	> 200 °C
Boiling point:	not applicable

Flash point:	not applicable
--------------	----------------

Evaporation rate:	The product is a non-volatile solid.
-------------------	--------------------------------------

Flammability (solid/gas):	Not a flammable solid according to UN transport regulations division 4.1 and GHS chapter 2.7. Based on the structure or composition there is no indication of flammability
---------------------------	--

Lower explosion limit:	For solids not relevant for classification and labelling.
------------------------	---

Upper explosion limit:	For solids not relevant for classification and labelling.
Ignition temperature:	not applicable
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated. Prolonged thermal loading can result in products of degradation being given off.
Self ignition:	not self-igniting
Self heating ability:	It is not a substance capable of spontaneous heating.
Explosion hazard:	not explosive
Fire promoting properties:	not fire-propagating
Vapour pressure:	not applicable
Density:	1.38 g/cm ³ (25 °C)
Relative vapour density (air):	not applicable
Solubility in water:	insoluble
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Viscosity, dynamic:	not applicable
Viscosity, kinematic:	not applicable, the product is a solid

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Conditions to avoid:

Temperature: > 300 °C

Prolonged exposure to elevated temperatures may result in exothermic decomposition accompanied by a pressure build-up in sealed containers. Avoid all sources of ignition: heat, sparks, open flame.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated. Prolonged thermal loading can result in products of degradation being given off.

Substances to avoid:

oxidizing agents

BASF 3D Printing Safety data sheet
Date / Revised: 03.09.2020
Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

No hazardous reactions if stored and handled as prescribed/indicated.

The product is chemically stable.

Hazardous decomposition products:

monomers, gases/vapours, hydrocarbons, oxides

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

Experimental/calculated data:

(oral):No applicable information available.

(by inhalation):The inhalation of dusts represents a potential acute hazard.

(dermal):No applicable information available.

Irritation

Experimental/calculated data:

Skin corrosion/irritation:May cause mechanical irritation.

Serious eye damage/irritation:May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity**Assessment of teratogenicity:**

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)**Assessment of repeated dose toxicity:**

Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

12. Ecological Information**Ecotoxicity****Assessment of aquatic toxicity:**

There is a high probability that the product is not acutely harmful to aquatic organisms.

Mobility**Assessment transport between environmental compartments:**

Study scientifically not justified.

Persistence and degradability**Assessment biodegradation and elimination (H₂O):**

Experience shows this product to be inert and non-degradable.

Bioaccumulation potential**Assessment bioaccumulation potential:**

Accumulation in organisms is not to be expected.

BASF 3D Printing Safety data sheet
Date / Revised: 03.09.2020
Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

Bioaccumulation potential:
Accumulation in organisms is not to be expected.

Additional information

Add. remarks environm. fate & pathway:
Due to the consistency of the product, dispersion into the environment is impossible. Therefore no negative effects on the environment may be anticipated based on the present state of knowledge.

13. Disposal Considerations

Must be disposed of or incinerated in accordance with local regulations.
A waste code in accordance with the European waste catalog (EWC) cannot be specified, due to dependence on the usage.
The waste code in accordance with the European waste catalog (EWC) must be specified in cooperation with disposal agency/manufacturer/authorities.

Contaminated packaging:
Packs that cannot be cleaned should be disposed of in the same manner as the contents.
Uncontaminated packaging can be re-used.

14. Transport Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Registration status:

BASF 3D Printing Safety data sheet
Date / Revised: 03.09.2020
Product: **Ultrafuse® PET Grey**

Version: 1.0

(11131818/SDS_GEN_PH/EN)

Date of print 09.01.2023

PICCS, PH

Listed or exempted.

16. Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.