

PBF Processing Guidelines

Please contact us at ultrasint-support@basf-3dps.com to receive the most updated version of print parameters dedicated to your material/machine combination.

In your email, include your SLS printer brand & model details, and the compatible* Ultrasint material you are willing to print with, and we will send you the complete print parameters matching your specific setup.

Printer Compatibility

		PP Line	PA11 Line					TPU Line			
		PP 1400 Black	PA 11	PA 11 Black	PA 11 CF	PA 11 rCF	PA 11 ESD	TPU01 for HP MUF	TPU 88A	TPU 88A Black	TPU 90A LT
HP	5200 Series							■			
Prodways	P1000 / P1000 S / P1000 X	□	□	□	□	□	□		□	□	□
3D Systems	Sinterstation / Vanguard / sPro 60	■	■	■	■	■	■		■	■	■
Nexa3D	QLS 230 / QLS 236 / QLS 260 / XYZprinting MfgPro Series		■	■	■	■	■		■	■	■
Farsoon	Flight Series	■		■	■	■				■	
	252P Series / 403P Series / eForm	■	■	■	■	■	■		■	■	■
EOS	P1 Series / P3 Series / P7 Series		□	□					□	□	□

* For the updated version of the Printer Compatibility list please refer to our [Material Catalog PBF](#).

PBF Material Onboarding Workflow

Our validated onboarding workflow guarantees seamless material onboarding for our customers. To receive more details, please contact us at ultrasint-support@basf-3dps.com.

